






# 350P

AGG. 10/20

3~ 50 Hz. 400V	
<b>PERKINS</b>	
EU STAGE 0	
69 dB(A) @ 7 mt	
400 lt	

PRIME POWER		STAND-BY POWER	
kVA	kW	kVA	kW
<b>350</b>	<b>280</b>	<b>385</b>	<b>308</b>

ENVIRONMENTAL CONDITIONS	
Temperature	<b>40° C</b>
Height	<b>1000 mslm</b>
Humidity	<b>60%</b>

**OPEN VERSION B400**
**SOUNDPROOF VERSION C450**


The image is only for demonstration purposes

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>3290</b>	<b>2950</b>	<b>1550</b>	<b>2100</b>

WEIGHT	DIMENSIONS		
	L [mm]	W [mm]	H [mm]
kg			
<b>4280</b>	<b>4300</b>	<b>1750</b>	<b>2350</b>


## TECHNICAL DETAILS

<b>ELECTRICAL DATA</b>	Electrical system type	3F+N	~
	Power factor	0,8	φ
	Voltage	400	V
	Frequency	50	Hz
	PRP Ampere rating	505	A
<b>ENGINE</b>	Engine	PERKINS 2206A-E13TAG2	
	Engine emissions standard (REG. UE 2016/1628)	EU STAGE 0	
	RPM governor	Electronic	
	Performance class (ISO8528-5)	G2	
	Rpm	1500	rpm
	Nr. of cylinders	6	
	Bore x stroke	130 x 157	mm
	Displacement	12500	cc
	Induction system	Turbocharged	
	Cooling system	Water	
	Engine net prime power	409 (305)	Hp (kW)
Exhaust gas aftertreatment	/		
<b>CONSUMPTION</b>	Fuel type	Diesel	
	Consumption @ 50-75-100% carico – load - charge	37 – 54 – 71	lt/h
	Standard tank capacity	400	lt
	Autonomy @ 75% carico – load - charge	7,4	h
<b>ALTERNATOR</b>	Alternator	STAMFORD – MECC ALTE – MARELLI MOTORI	
	Type	Self excited, brushless	
	Number of poles	4	
	Insulation class	H	
	Temperature rise class	H	
	Voltage regulation	AVR	
	Voltage precision	± 1	%
<b>GENERAL</b>	Sound level (soundproof version)	69	dB(A) 7mt
	Exhaust pipe diameter	200	mm
	Electrical system voltage	24	V

## ELECTRIC PANEL

MANUAL

AUTOMATIC MAINS FAILURE



Electronic control unit with multimeter	COMAP AMF25	COMAP AMF25
Electrical panel enclosure protection degree	IP44	
ON-OFF electric panel switch	Key type	Without key
Emergency pushbutton	STANDARD	
Battery charge maintainer	/	24V 5A
Power supply	Full power terminal	Full power terminal
Circuit breaker	Magnetothermal type 4P ABB Tmax-T 630A	Magnetothermal type 4P ABB Tmax-T 630A
Main protection alarms	Min-max V and Hz. LOP. HWT. Battery charger alternator failure. Low fuel level	

## STANDARD ELECTRONIC CONTROL UNIT

COMAP  
AMF25



Functions: automatic or manual start, remote start, periodic test

Multimeter V (L1, L2, L3, N), A (L1, L2, L3), Hz, kVA, battery V, hour counter

Backlit LCD display. USB port

Communication accessories available: Ethernet, GSM-GPRS, 4G, GPS

MODBUS and SNMP communication protocols support

Advanced PLC configurability


## OPTIONAL ELECTRONIC CONTROL UNIT



DEEP SEA DSE7320 MKII

**SOUNDPROOF AND WEATHERPROOF CANOPY**



<i>Self-supporting frame material</i>	<i>Carbon steel sheet, electro-welded, minimum thickness 4 mm</i>
<i>Soundproof canopy material</i>	<i>Carbon steel sheet, electro-welded, thickness between 2 and 9 mm</i>
<i>Painting</i>	<i>Epoxy powder RAL5015 textured, outdoor-proof</i>
<i>In-built fuel tank</i>	<b>400 lt + Drip tray</b>
<i>Soundproofing coating material</i>	<i>Polyester fiber. Fire resistance EN13501-1 class B</i>
<i>Muffler</i>	<i>In-built the canopy. Residential type with sound reduction 35 dB(A)</i>
<i>Access openings</i>	<i>n.4 doors with padlockable key lock</i>
<i>Electric panel</i>	<i>Lateral side position. Dedicated door with key lock</i>
<i>Fresh air intake and hot air expulsion</i>	
<i>Lifting system</i>	<i>n.4 lifting hooks</i>
<i>Support feet</i>	<i>n.4 support feet with holes for machine ground fastening</i>

## MAIN OPTIONS



630A automatic transfer switch (ATS)



600 lt bigger fuel tank with drip tray



2250W engine preheating system



Automatic fuel transfer kit with manual by-pass system



Residual current protection relay adjustable in sensitivity and intervention time

## OTHER OPTIONS

Power distribution socket set

Synchronizing electric panel

Battery switch

Remote control systems **ETHERNET, 2G - 3G - 4G, GPS**

Further alternator brand

Quick couplings for connecting an external tank with three way valve

Outdoor, underground and transportable tanks

Slow or fast towing trailer

Front hot air expulsion canopy

Further colors

**Greenpower AB**

Helsingborgsvägen Varalöv,

262 96 Ängelholm, Sweden

Phone: +46 43122240

Email: [info@greenpower.se](mailto:info@greenpower.se)

Web: [www.greenpower.se](http://www.greenpower.se)